

PRODUCT INFORMATION



HT-12® and Frostox are brands
of HAERTOL Chemie

Automotive Chemicals – Antifreeze Coolant

Version: 2020/45#1c

Valvoline™ HT-12™ ANTIFREEZE COOLANT Green

VALVOLINE HT-12 is the latest patented* coolant technology approved by BMW, MINI and Rolls-Royce.

Valvoline HT-12 Antifreeze Coolant Green is a superior engine coolant developed to fulfil the latest requirements of most high performance engines and provide an extended service life up to 5 years or 250.000 km.

This Si-OAT formulation incorporates state-of-the-art organic acid technology in an ethylene glycol base for excellent protection of all cooling system components and metals including aluminum. Valvoline HT-12 Green is free of phosphates, nitrites, amines and borates and is compatible even with tap water.

When concentrate diluted 50% with water, Valvoline HT-12 Antifreeze Coolant Green protects modern engine components from winter freezing and summer boiling. The chart below provides detailed mixing information and minimum water quality requirements.

Approvals
BMW LC-18
Performance levels
ASTM D3306
ASTM D4985
ASTM D6210
AS 2108-2004
BS 6580:2010
Cummins CES 14603, CES 14439

Performance levels
CUNA NC 956-16
Deutz DQC CC-14
GB 29743-2013
JIS K 2234:2006
ONORM V 5123
PN-C40007:2000
SANS 1251:2005

Features and Benefits

Patented* formula for superior protection

Valvoline HT-12 Green coolant is a premium grade coolant that provides outstanding protection to vital engine parts such as coolant channels in engine block, cylinder heads (liner pitting), radiator and water pump against corrosion, overheating and frost. It contains a high quality defoamer and will not harm gaskets, hoses, plastics or original vehicle paint.

*Patent no EP2744869B1

OEM approved coolant

Valvoline HT-12 Antifreeze Coolant Green is approved by BMW according to the LC-18 specification.

TRUSTED FOR 150 YEARS™

VALVOLINE EUROPE
WIELDRECHTSEWEG 39
3316 BG DORDRECHT
NETHERLANDS

PRODUCT INFORMATION



Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit www.valvolineeurope.com or <https://pisheets.valvoline.com/>

Typical properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline specifications, variations in these characteristics may occur.

Valvoline HT-12 Antifreeze Coolant Green	
Appearance	Liquid
Colour	Green
Reserve alkalinity* (ml), ASTM D1121	>10
Boiling point* (°C), ASTM D1120	>170
Density* g/cm ³ @20°C, ASTM D1122	1,123 – 1,128
pH value (50 vol%), ASTM D1287	8,3 – 8.6
Storage stability	Up to 5 years

* Concentrate ** When diluted 50/50 with water

Material numbers

Packaging	Concentrate	Ready to use
12/1L		889279
4/5L		896129
60L KE	889238	

This information only applies to products manufactured in the following location(s): Europe

™ Trademark of Valvoline, registered in various countries © 2022

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Ellis Enterprises B.V. and its affiliates assume legal responsibility.

Health & Safety

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet.

<http://sds.valvoline.com>

Protect the environment

Take used coolant to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.

Storage

We recommend storing all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

Valvoline HT-12 Concentrate Green Mixing Table	
Concentrate mixed with water	Freezing Point °C
40% concentrate	-24
50% concentrate	-36
60% concentrate	-48
70% concentrate*	-67

*Maximum freeze protection is at 70%

Minimum Water Quality Requirements	
Parameter	Requirement
pH value	6,0 - 8,0
Water hardness, °dH	< 20
Conductivity, µS	100 - 400
Calcium, mg/l	< 60
Copper, mg/l	< 0,1
Sulfate, mg/l	< 50
Chloride, mg/l	< 40
Iron, mg/l	< 0,2
Fluoride, mg/l	< 50

TRUSTED FOR 150 YEARS™

VALVOLINE EUROPE
WIELDRECHTSEWEG 39
3316 BG DORDRECHT
NETHERLANDS