

INEOS Grenadier Quick Ref Guide Fluids / Specifications

Front Axle		Specification			
		Min	Nom	Max	
Toe	Left	0'	0'	0'	
	Right	0'	0'	0'	
	Total	0'	0'	0'	
Camber	Left	-40'	0'	+40'	
	Right	-40'	0'	+40'	
Caster	Left	1° 24'	2° 00'	2° 36'	
	Right	1° 24'	2° 00'	2° 36'	
Max. Inner Wheel Angle	Left Turn	32° 30'	33° 00'	33° 30'	
	Right Turn	32° 30'	33° 00'	33° 30'	
Rear Axle		Specification			
Toe	Left	-25'	+0'	+25'	
	Right	-25'	+0'	+25'	
	Total	-25'	+0'	+25'	
Camber	Left	-30'	0'	+30'	
	Right	-30'	0'	+30'	
Thrust Angle	Total	-12'	0'	+12'	
Tyre Size	LT 265/70R17 S		LT 255/70R18 S		
Tyre Pressures					
Front / Rear U/L	2.5 / 2.5 Bar	36 / 36 PSI	2.5 / 2.5 Bar	36 / 36 PSI	
Front / Rear L	3.0 / 3.4	43.5 / 49 PSI	3.0 / 3.4 Bar	43.5 / 49 PSI	
Spare	3.4 Bar	49 PSI	3.4 Bar	49 PSI	
Wheel Nut Torque	Alloy	160Nm	Steel	160Nm	
Brake Disc's					
	Min Thickness	Max thickness	Diameter	Internal Diameter	
Front Disc	25mm	28mm	316mm	198mm	
	Min Thickness	Max Thickness	Diameter	Internal Diameter	
Rear Disc	10mm	12mm	305mm	200mm	
Glass Tint	%	%			